


### 3<sup>rd</sup> Generation thinQ!<sup>TM</sup> SiC Schottky Diode

#### Features

- Revolutionary semiconductor material - Silicon Carbide
- Switching behavior benchmark
- No reverse recovery / No forward recovery
- Temperature independent switching behavior
- High surge current capability
- Pb-free lead plating; RoHS compliant
- Qualified according to JEDEC<sup>1)</sup> for target applications
- Breakdown voltage tested at 20mA<sup>2)</sup>
- Optimized for high temperature operation
- Lowest Figure of Merit  $Q_C/I_F$
- Halogen-free according to IEC 61249-2-21 definition

#### Product Summary

$V_{DC}$	600	V
$Q_C$	6	nC
$I_F; T_C < 130\text{ °C}$	5	A

**PG-T0252-3**


#### thinQ! 3G Diode designed for fast switching applications like:

- SMPS e.g.; CCM PFC
- Motor Drives; Solar Applications; UPS

Type	Package	Marking	Pin 1	Pin 2	Pin 3
IDD05SG60C	PG-T0252-3	D05G60C	n.c.	A	C

#### Maximum ratings

Parameter	Symbol	Conditions	Value	Unit
Continuous forward current	$I_F$	$T_C < 130\text{ °C}$	5	A
Surge non-repetitive forward current, sine halfwave	$I_{F,SM}$	$T_C = 25\text{ °C}, t_p = 10\text{ ms}$	26	
		$T_C = 150\text{ °C}, t_p = 10\text{ ms}$	18	
Non-repetitive peak forward current	$I_{F,max}$	$T_C = 25\text{ °C}, t_p = 10\text{ }\mu\text{s}$	150	
$i^2t$ value	$\int i^2 dt$	$T_C = 25\text{ °C}, t_p = 10\text{ ms}$	3.2	A <sup>2</sup> s
		$T_C = 150\text{ °C}, t_p = 10\text{ ms}$	2	
Repetitive peak reverse voltage	$V_{RRM}$	$T_j = 25\text{ °C}$	600	V
Diode dv/dt ruggedness	dv/dt	$V_R = 0 \dots 480\text{ V}$	50	V/ns
Power dissipation	$P_{tot}$	$T_C = 25\text{ °C}$	56	W
Operating and storage temperature	$T_j, T_{stg}$		-55 ... 175	°C
Soldering temperature, reflow soldering (max)	$T_{sold}$	reflow MSL1	260	

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

**Thermal characteristics**

Thermal resistance, junction - case	$R_{thJC}$		-	-	2.7	K/W
Thermal resistance, junction - ambient	$R_{thJA}$	SMD version, device on PCB, minimal footprint	-	-	75	
		SMD version, device on PCB, 6 cm <sup>2</sup> cooling area <sup>5)</sup>	-	50	-	

**Electrical characteristics, at  $T_j=25\text{ °C}$ , unless otherwise specified**
**Static characteristics**

DC blocking voltage	$V_{DC}$	$I_R=0.05\text{ mA}$ , $T_j=25\text{ °C}$	600	-	-	V
Diode forward voltage	$V_F$	$I_F=5\text{ A}$ , $T_j=25\text{ °C}$	-	2.1	2.3	
		$I_F=5\text{ A}$ , $T_j=150\text{ °C}$	-	2.8	-	
Reverse current	$I_R$	$V_R=600\text{ V}$ , $T_j=25\text{ °C}$	-	0.4	30	$\mu\text{A}$
		$V_R=600\text{ V}$ , $T_j=150\text{ °C}$	-	1.5	350	

**AC characteristics**

Total capacitive charge	$Q_c$	$V_R=400\text{ V}$ , $I_F \leq I_{F,max}$ , $di_F/dt=200\text{ A}/\mu\text{s}$ ,	-	6	-	nC
Switching time <sup>3)</sup>	$t_c$	$T_j=150\text{ °C}$	-	-	<10	ns
Total capacitance	$C$	$V_R=1\text{ V}$ , $f=1\text{ MHz}$	-	110	-	pF
		$V_R=300\text{ V}$ , $f=1\text{ MHz}$	-	15	-	
		$V_R=600\text{ V}$ , $f=1\text{ MHz}$	-	15	-	

<sup>1)</sup> J-STD20 and JESD22





<sup>2)</sup> All devices tested under avalanche conditions, for a time periode of 10ms, at 20mA.

<sup>3)</sup>  $t_c$  is the time constant for the capacitive displacement current waveform (independent from  $T_j$ ,  $I_{LOAD}$  and  $di/dt$ ), different from  $t_{rr}$  which is dependent on  $T_j$ ,  $I_{LOAD}$  and  $di/dt$ . No reverse recovery time constant  $t_{rr}$  due to absence of minority carrier injection.

<sup>4)</sup> Under worst case  $Z_{th}$  conditions.


<sup>5)</sup> Device on 40mm\*40mm\*1.5 epoxy PCB FR4 with 6cm<sup>2</sup> (one layer, 70 $\mu\text{m}$  thick) copper area for drain connection. PCB is vertical without blown air

<sup>6)</sup> Only capacitive charge occuring, guaranteed by design.

**1 Power dissipation**
 $P_{tot}=f(T_C)$ ; parameter:  $R_{thJC(max)}$ 

**2 Diode forward current**
 $I_F=f(T_C)^4$ ;  $T_j \leq 175$  °C; parameter:  $D = t_p/T$ 

**3 Typ. forward characteristic**
 $I_F=f(V_F)$ ;  $t_p=400$   $\mu$ s; parameter:  $T_j$ 

**4 Typ. forward characteristic in surge current mode**
 $I_F=f(V_F)$ ;  $t_p=400$   $\mu$ s; parameter:  $T_j$ 



**5 Typ. capacitance charge vs. current slope**

$$Q_C = f(di_F/dt)^6; I_F \leq I_{F,max}$$




**6 Typ. reverse current vs. reverse voltage**

$$I_R = f(V_R); \text{parameter: } T_j$$




**7 Transient thermal impedance**

$$Z_{thJC} = f(t_p); \text{parameter: } D = t_p/T$$




**8 Typ. capacitance vs. reverse voltage**


$$C = f(V_R); T_C = 25 \text{ °C}, f = 1 \text{ MHz}$$



**9 Typ. C stored energy**

$$E_C = f(V_R)$$



**PG-T0252-3: Outline**


DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	2.16	2.41	0.085	0.095
A1	0.00	0.15	0.000	0.006
b	0.64	0.89	0.025	0.035
b2	0.65	1.15	0.026	0.045
b3	5.00	5.50	0.197	0.217
c	0.46	0.60	0.018	0.024
c2	0.46	0.98	0.018	0.039
D	5.97	6.22	0.235	0.245
D1	5.02	5.84	0.198	0.230
E	6.40	6.73	0.252	0.265
E1	4.70	5.21	0.185	0.205
e	2.29		0.090	
e1	4.57		0.180	
N	3		3	
H	9.40	10.48	0.370	0.413
L	1.18	1.70	0.046	0.067
L3	0.90	1.25	0.035	0.049
L4	0.51	1.00	0.020	0.039
F1	10.50	10.70	0.413	0.421
F2	6.30	6.50	0.248	0.256
F3	2.10	2.30	0.083	0.091
F4	5.70	5.90	0.224	0.232
F5	5.66	5.86	0.223	0.231
F6	1.10	1.30	0.043	0.051

DOCUMENT NO.  
Z8B00003328

SCALE

EUROPEAN PROJECTION

ISSUE DATE  
19-10-2007

REVISION  
03

Dimensions in mm/inches

**Published by**  
**Infineon Technologies AG**  
**81726 Munich, Germany**  
**© 2008 Infineon Technologies AG**  
**All Rights Reserved.**

**Legal Disclaimer**

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

**Information**

For further information on technology, delivery terms and conditions and prices, please [contact the nearest Infineon Technologies Office \(www.infineon.com\)](http://www.infineon.com).

**Warnings**

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office. Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.